



XR 212-68

Refrigeration Lubricant

Product Description

XR 212-68 is a high performance refrigeration compressor lubricant based on a premium naphthenic mineral oil. The excellent stability and low temperature properties make this product ideal for a wide variety of refrigeration applications. XR 212-68 is wax free which prevents solid formation in the evaporator and expansion valve.

Applications*

- R-22
- R-123
- R 414A

* To assure proper lubricant selection, please consult your Xaerus Performance Fluids representative

Health and Safety

Based on available information, XR 212-68 is a non-toxic, non-hazardous product that is not expected to cause any adverse health effects when used as designed. Users are advised to follow the recommendations provided in the MSDS.

Typical Properties

Criteria	Value	Method
Viscosity, cSt @ 40° C	67.7	ASTM D-445
Viscosity, cSt @ 100°C	7.0	ASTM D-445
Viscosity Index	37	ASTM D2270
Flash Point, °F/°C	404/206	ASTM D-92
Pour Point, °F/°C	-22/-30	ASTM D-5950
Moisture, ppm	20	ASTM D-6304
Specific Gravity @ 77°F/25° C	0.909	ASTM D-4052
Density, lb/gal	7.58	ASTM D-4052
Color	0.5	ASTM D-1500
Aniline Point, °F/°C	194/90	ASTM D611

Notice: The information and statements above are based on information we believe to be reliable; however, we expressly do not represent, warrant or guarantee the accuracy, completeness, or reliability of the same.